LAND RECLAMATION -- CHECKLIST MINED

TITLE 40-8 UCA 1953 GENERAL RULES AND REGULATIONS RULES OF PRACTICE AND PROCEDURE

		INCLUDED		
CITATION	REGULATION	IN PLAN	ADEQUATE	COMMENTS
	LEGAL, FINANCIAL	- E		
1-3/MR 1/1.	Name of Applicant			
1-3/MR 1/2.	Address			
4-3/MK 1/2.	Permanent Temporary			
M-3/MR 1/3.	Company Representative Name Title	~	i	
M-3/MR 1/4.	Address Office Phone			
M-3/MR 1/5.	Location County Township/Range/Section			
1-3/MR 1/6.	Name of Mine			
4-3/MR 1/7.	Mineral to be Mined			
M-3/MR 1/8.	Other Approvals/Listed			
M-3/MR 1/9.	Owners of Record of Land Affected		. /	
M-3/MR 1/10.	Owners of Record of Minerals to be Mined			should minerale rights ownership be
M 2 /MD 1 /11	Owners of Percent of all Other Minerals			rights ownership be

Owners of Record of all Other Minerals

M-3/MR 1/11.

		DOGM LEAD REV	/IEWER
ATNE			

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
M-3/MR 1/11a.	Notification of Other Owners in Writing			Patentel unpatented claim
M-3/MR 1/12.	Legal Right to Enter & Conduct Operations			ok ok
M-3/MR 1/13.	Acreage 1.` Operation Area 2. Access Road or Haulways 3. Drainage System 4. Total Land Affected			
M-3/MR 1/14.	Principal Executives, Officer & Partners Name Title			
	Address			
M-3/MR 1/15.	Previous Notice of Intention Withdrawn			
M-3/MR 1/16.	Signed			
	MAPS AND PLANS			
M-3(1)	True Copy Map or Plat			
M(3)(1)(a)	Land Affected Delineation			
M(3)(1)(b)	Within Land Affected Existing Mine Areas Active Abandoned (prior to May, 1975) Boundaries of Surface Properties			
	Names of Surface Owners Names of Mineral Owners		V V	

DOGM LEAD REVIEWER

الأراد المنابس المنابس المنابس		INCLUDED		
CITATION	REGULATION	IN PLAN	ADEQUATE	COMMENTS
M-2	"Land Affected means the surface and subsurface of an area within the state where mining operations are being or will be conducted, including, but not limited to: on-site private ways, roads, and railroad lines appurtenant to any such area; land excavations; exploration sites; drill sites or workings; refuse banks or spoil piles; evaporation or settling ponds; leaching dumps; placer areas; tailings ponds or dumps; work parking, storage, or waste discharge areas; areas in which structures, facilities, equipment, machines, tools or other materials or property which result from or are used in such operations, are situated. All lands shall be excluded that would be otherwise includable as land affected but which have been reclaimed in accordance with an approved plan or otherwise, as may be approved by the Board, and lands in which mining operations have ceased prior to July 1, 1977."			
M-3(1)(c) M6	"All maps and plans prepared for submission with the Notice of Intention to Commence Mining Operations shall be of adequate			

MINE	DOGM LEAD REVIEWER	

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
M-3(1)(c) M6 (continued)	scale and detail to show topographic features and clearly indicate details of the proposed operations in accordance with Rule M-3. A color code, or other legend, shall be used in preparing all maps to clearly indicate surface features of the land affected."			
M-3(1)(d)	Names and Locations Lakes, Rivers, Streams, Creeks Roads, Buildings Active, Abandoned Facilities Transmissions Lines (within 500 feet)			
M-3(1)(e)	Drainage Plan Overburden, Topsoil, Waste Stockpiles Directional Flow Constructed Drainways, Diversions, Berms Receiving Waters			
M-3(1)(f)	Drill Holes Location Status Depths and Thickness Water Bearing Strata Mineral Deposits Toxic Materials Revegetation Materials (topsoil)		2	holost present status on plugginger aleneoust
M-3(1)(g)	Locations of Disposal and Stockpile Areas Topsoil Storage Overburden Materials Waste, Tailings, Rejected Materials Tailings-Ponds Discharge Points, Water Effluents			

MINE	DOGM LEAD REVIEWER	

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
	EFFLUENT CONTROL			
M-10/11	Methods for Controlling Sediment			
M(3)(3)(11)	"Sediment Control—Mining operations shall be conducted in a manner such that sediment from areas disturbed in mining or reclamation activities is adequately controlled. The degree of sediment control shall be appropriate for the site-specific and regional conditions of topography, soil, drainage, water quality, or other characteristics."			
M-3(1)(h)	Description of Water to be Disposed Expected Acid or Salt Content Expected Toxicity Expected Impact on Downstream Waters Description of Discharge Permits			
M-3(3) M-3(3)/MR 1-7 MR 2-7	OPERATION PLAN/SITE CONSTRUCTION Mining Method General Details If Sedimentary Deposit Seam Thickness Dip Outcrop	N/	a	
MR 2-11(1)	Mining Sequence			
MR 2-11(b)	Construction and Maintenance of Access Roads Procedures Cross-section Profile			

MINE		DOGM LEAD REVIEWER		
CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
MR 2-11(c)	Site Preparation Trees Brush			Not covered with ma
M-3(2)c MR 2-11(d)	Topsoil, Root Growth, Medium			49 Them
MR-2/11(c)	Methods for Removal Amounts of Topsoil Removed — ask for Methods of Topsoil Protection		Sol see P.	almounts lette, at stockpile, need for est at reclamical
M-10(14)	"Soils—Except where slope or rocky rocky terrain make it impossible, all surficial materials, suitable as a growth medium, prior to any major excavation, shall be removed, segregated, and stockpiled according to its ability to support vegetation as determined by soil analysis and/or practical revegetation experience. The stockpiles shall be protected in such a manner as to minimize or prevent wind and water erosion, unnecessary compaction, and contamination by undesirable materials. Redistribution and surficial material after final grading shall be accomplished in such a manner as to promote revegetation success."		Jaros Plante	
M-3(2)c MR 2-11(e)	Disturbed and Excess Materials Tailings, Waste and Reject Handling Method of Placement and Containment Stability and Erosion Control Overburden Method of Placement and Containment Stability and Erosion Control			Solid waste disposal in sandan fandil, where?

Toxic, Acid/Alkali Producing Materials

MINE	DOGM LEAD REVIEWER	

****************************	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
R-2/10.	Determination as Toxic, Acid, Alkali Testing Procedure and Results	V V		
4-2 K(6)	"Toxic means any chemical or biological or adverse characteristic of the material involved which could reasonable be expected to negatively affect ecological or hydrological systems or could be hazardous to the public safety and welfare."	V		
1– 10(6)	"Toxic Materials—All toxic or potentially toxic material, as defined by Rule M-2(k), shall be safely removed from the site or left in an isolated condition such that solid, liquid or gaseous toxic emissions to the environment are reasonably eliminated or controlled. Such isolation practices	_	7,	what will be done of withing reclamation.
	may inlude, but not be limited to, burial, subsurface injection, chemical precipitation or neutralization, and filtering. All appropriate regulations of the Division of Health must be complied with as well as Federal regulations."			
M-3(2)(c) MR-2/11(e)	Method of Placement and Containment Stability and Erosion Control			

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
M-3(2)	RECLAMATION PLAN			
M-10	"The following reclamation standards are established where applicable for all work or activity required to be performed in accordance with reclamation plans approved subsequent to June 1, 1978. Mine workings abandoned prior to May, 1975, need not be reclaimed unless said workings are utilized for subsequent operations. Areas on which these standards are proposed to be non-applicable will be designated on the maps submitted by this operator in accordance with Rule M-6, and may be shown on supplementary ground or air photographs.			
	Said standards shall apply to all operators covered by a mining and reclamation plan and variances to all portions herein will be considered on a site-specific basis by the Division and/or Board."		-	
M - 2i	"Reclamation means actions peformed during or after mining operations to shape, stabilize, revegetate, or otherwise treat the land affected in order to achieve a safe, stable, ecological condition and use which will be consistent with local environmental conditions."			

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
M-3(2)/MR 2,3	Land Uses			
M-3(2)(a)	Prior Land Uses			
M-3(2)(a)	Current Uses			
4-3(2)(b)	Potential Uses			
M-10(1)	"Land UseThe operator shall abandon the area affected in a condition which is capable of supporting a postmining use that is compatible with probable land uses."			- all an
1-3(2)/MR 2-4	Existing Vegetation Percent Cover		yes .	combine all con values = 42.37
M-3(2)/MR 2-5	Existing Soils		Oi	X.I
1-3(2)/1111 2-3	pH Solls			79.66
	Soil Lab Reference			221
1-3(2)/MR 2-6	Site Elevation			regue
1-3(2)/1111 2-0	Site Abandonment	~		The state of the s
				70,7
M-10(2)	"Public Safety and WelfareThe			40,
	operator shall minimize hazards			1 200
	to the public safety and welfare	A CONTRACTOR OF THE CONTRACTOR		000.
	following mining. Methods to			
	minimize hazards shall inloude but not be limited to:			
	(a) The closing of shafts and tunnels to prevent unauthorized or accidental entry.			

DOGM LEAD REVIEWER MINE INCLUDED COMMENTS ADEQUATE IN PLAN REGULATION CITATION (b) The disposal of trash, scrap M-10(2)metal and wood, unuable buildings (continued) extraneous debris and other materials incident to mining in a manner approved by the Division and in accordance with the Rules and Regulations of the Division of Health. (c) The plugging and capping of drill, core or other exploratory holes as set forth in Rule M-3(5). (d) The posting of appropriate warning signs in locations where public access to operations is readily available. (e) The construction of berms, fences and/or barriers above highwalls or other excavations when required by the Division." resnoval necessary Structure Removal "Structures and Equipment--All M-10(9)structures, rail lines, utility connections, equipment, and debris shall be removed from the surface prior to regarding and reclamation unless temporarily abandoned or approved by the Division for a continuing use." explosives use permits clarification Rules ?

MINE	DOCH LEAD DEUTEUED	
MINE	 DOGM LEAD REVIEWER	

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
M-3(2)(d) MR-2(f)	Procedures and Methods For Final Stabilization and Regrading	/		
MR-2(a)	Typical Cross-section of Regraded areas Specific Description of Regrading areas			Discriptions provides adequate junterstanding
M-10(10)	"Shafts and Portals—All shafts and portals shall be covered or closed and all trenches and small pits shall be backfilled or covered when a mine has been abandoned so as to eliminate any safety hazard.			
	Roads and Pads—On-site roads and pads shall be reclaimed or stabilized when the operator determines that they are no longer needed for mining operations. The reclamation should include provisions for adequate surface drainage protection and unrestricted drainage crossings. When a road or pad is to be turned over to an approved continuing use, as determined by the operator, the operator shall turn over the property with adequate surface drainage, drainage structures, ditching, and in a general condition suitable for the continued use.			
	HighwallsIn strip mining or open pit mining and in open cuts for pads or roadways all such highwalls shall be reclaimed by backfilling			

DOGM LEAD REVIEWER

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
Highwalls (sorthroad) MR-2(e)	against them or by cutting the wall back to achieve a slope angle of 45 or less. Where the highwall is composed of solid rock; is designed to be stable utilizing benches, tie-backs, etc.; or, there is insufficient material reasnably available to backfill; or cutting the wall back would result in excessive damage to undisturbed land above the highwall; and taking into consideration suitable alternative safety measures; future land use, etc.; the Division may modify or waive the above requirements." Description of Maximum Slope Grades			sufficient? design
	"SlopesAll waste piles, spoil piles, and fills shall, if possible, be regraded to a rounded configuration and they shall be sloped to minimize safety hazards and erosion. The angle of slope from the bottom to the top of the pile or fill can be greater than the surrounding terrain provided that the mass stability of the slope is assured and that the erosion of the slope is minimized by measures such as, but not limited to; terracing, surface drainage facilities, cross-slope ripping or scarifying and vegetation. In no case shall the slope of a pile or fill exceed the angle of repose of			

MINE			DOGM LEAD REVIEWER		
CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS	
Slopes (continued)	the material or such lessor slope as required by the Division considering such factors as: land use, material properties, revegeta- tion potential or erosion control."				
MR-2(1)	Description of Determining Stability of Reclaimed Fill Material	2		whe for	
MR-2(f)	Description of the Method of Drainage Control for Regraded Areas				
	"DrainagesAll natural channels and associated flood plains shall not be covered, restricted or rerouted by roads, pads, piles, fills or diversions unless specifically approved by the Division after a suitable hydrologic				
	study and incorporating a sound hydraulic design. All drainage structures, sediment or flood control structures, spoil, ore, waste, fill material and debris must be removed from natural channels and flood plains before an operator abandons the site except where approved by the Division.				
	ONE DIAISION.				

MINE DOGM LEAD REVIEWER

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
M-10(13)	DamsAll major water impounding structures such as tailings, dams, water storage and supply dams, coal waste dams and major sedimentation control dams shall be reclaimed when abandoned so as to be nonimpounding, self-draining, mechanically stable and protected from erosion. ImpoundmentsAll evaporation,			
4-10(3)	tailings and sediment ponds; spoil piles, fills, pads and regraded areas shall be self-draining and nonimpounding when abandoned unless previously approved as an impounding facility by a lawful state or federal agency."			Is settling pond uses for wildlife upon water alright?
MR-2(10)	Topsoil Distribution Plans Specific Description of Spreading Topsoil/ Growth Medium Approximate Thickness of Topsoil/Growth Medium		7.	ask Hen for
MR-2(3)	Description of Surface Preparation Revegetation Plans			calculations a
MR-2(1)	Who Will Complete Revegetation? Seed Bed Preparation			P. 2-46, by of region of Removed Re

DOGM LEAD REVIEWER

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
MR-2(1)	Description of Soil Treatments to Aid Revegetation			
M-10.12	"Practial land treatments may include but not be limited to: scarifying, mulching, fertilization, irrigation, chisel plowing, harrowing and the introduction of soil mycorrhiza.			The description of
M-10.12	Description of Method for Testing Soil to Support Vegetation Fertilization Plans		7 8	test plots "adequate? in lest
MR-2-2.	Mulch Type Rate/Acre	Mulah	test Plot	are description of test plots "adequate? included in test are being whilised in revenue of attornal are points afternal of the series of attornal of the series of the ser
	Seeding	to der		
M-3(2)(e()	"A planting program as best calculated to revegetate the land affected. Where there is no original protective cover, an alternate practical procedure should be proposed to minimize or control erosion or siltation. When applicable, the objective in revegetation should be to stabilize the land as quickly as possible after it has been disturbed in order to achieve permanent and protective vegetative cover. Non-noxious native plants that will give a quick, permanent, protective cover and enrich the			

MINE	DOGM LEAD REVIEWER	

CITATION	REGULATION	INCLUDED IN PLAN	ADEQUATE	COMMENTS
MR 2-1	Description of Seeding Method			
MR 2-3	Justification of Seed Mix			
M- 10(12)	"RevegetationWhere possible, a self-sustaining vegetative cover consisting of non-noxious perennial plants shall be established by the operator subsequent to final grading on the entire area affected.			
	Plants shall be a diverse mixture of grasses, shrubs, forbs and where potential for forestation exists, trees; the mixture may include both native and introduced species. Revegetation shall be performed using professionally accepted methods such as seeding, transplanting or propagating by cuttings.			
	(1) The species selection shall reflect the post-mining land use as set forth in Rule M-10(1)			
MR-2 3.	U. S. Soil Conservation Service		7	
MR-2 3.	Test Plots Use of Seed Mix			
MR-2 3.	Description of Application Location/Facing (bearing) Rate Per Acre (PLS) Species Mix Per Location Season to be Planted Maintenance/Monitoring	de	W.	Auh?

DOGM LEAD REVIEWER MINE INCLUDED COMMENTS ADEQUATE IN PLAN REGULATION CITATION MR-2/5. Description of Irrigation Methods To Establish Vegetation Inspections Frequency 3 Purpose Livestock Grazing Fencing Vegetation Protection M-3(2)(f)Reclamation Schecule Speaketimes not given? Estimated Time for Construction Estimated Time for Interim Reclamation Estimated Duration of Mining Operation MR-2 8. A Time Table for the Accomplishment of M - 3(2)f2 Each Major Step in Reclamation Plans M-5 Reclamation Surety Estimate Estimate Based on Reclamation Plan Cleanup and Removal of Structures Grading and Contouring Stabilization Labor Safety and Fencing Monitoring M - 3Standard of Reclamation Success "(2) Revegetation shall be deemed to be accomplished and successful when: (a) Species intented for revegetation by this Rule have achieved a surface cover of at least 70% of the representative vegetative communities surrounding the mine. Surrounding

vegetative cover levels shall be

**********		IN	CLUDED		
CITATION	REGULATION	IN	PLAN	ADEQUATE	COMMENTS
(a) (continued)	determined by the operator using professionally accepted inventory methods and be approved by the Division. (b) The vegetation initiated on the area affected has survived for at least three (3) growing seasons, is evenly distributed, and is not supported by irrigation or continuing soil amendments.				
	(3) Exceptions to Part 12 may be granted by the Division for areas which consist of solid rock outcrops and it is deenstrated by the operator that sufficient surficial soil does not exist for covering said outcrops. Test plots established by the operator in consultation with the Division shall demonstrate after all practical land treatments have been attempted that the revegetation standards are not attainable."		you vo	at regulation	estapt.
M-10 MR-8	Commitment to Rule M-10.				• •